

FENCE CELLULAR GATEWAY FOR REMOTE CENTRAL CONTROL AND MANAGEMENT OF SMART ENERGIZERS



www.fencee.eu

(**) FENCE GATEWAY GWC300

- Power supply via network adapter and battery backup in case of power failure
- Internet control is not limited by distance
- · One gateway can control up to 20 devices
- Always up-to-date software with the possibility of upgrading over internet

EENCE CELLULAD

	FENCE CELLULAR GATEWAY GWC300
POWER SUPPLY	230 V / 50 Hz, 14 VDC
CONSUMPTION	max. 300 mA
BACKUP BATTERY	3,6 V
LED INDICATION	~
ALARM SYSTEM	~
EXTERNAL CONNECTOR SMA	~
NUMBER OF CONNECTED DEVICES	up to 20
RANGE WITH BASIC ANTENNA	up to 10 km
RANGE WITH EXTERNAL ANTENNA	up to 30 km
TRANSMISSION FREQUENCY	869,525 MHz
TRANSMITTING POWER RF	+22 dBm
TRANSMITTING POWER LTE	+22 dBm
TRANSMITTING POWER BLUETOOTH	+6 dBm
LTE	~
Cat M1	~
NB-IoT	~
2G	~
GPS	~
BLUETOOTH	2,4 GHz
DIMENSIONS	78 × 144 × 42 mm
WEIGHT	380 g

fence Electric fencing

www.**fencee**.eu